



SkyTest

Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)
Issue date: 5/7/2025 Version: 1.0

SECTION 1 Identification

1.1. Product identifier

Product form : Mixture
Trade name : SkyTest
Product code : SKYTEST

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Use of the substance/mixture : Lubricant Testing
Restrictions on use : None known

1.4. Supplier's details

TBM, Inc.
8506 Herrington Ct.
Pevely, MO 63070
T 1-314-721-2888 / 1-800-721-2888
scoleman@fsptbm.com

1.5. Emergency phone number

Emergency number : For Hazardous Materials or Dangerous Goods Incident Spill, Leak, Fire, Exposure, or Accident
Call CHEMTREC Day or Night: 1-800-424-9300 (Toll Free, USA) / 703-527-3887 (Virginia, USA)
CCN 21826
Back-up Emergency Number: +1 703-741-5970 (Washington, DC)

SECTION 2 Hazard Identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquid, Category 2	H225	Highly flammable liquid and vapor.
Skin corrosion/irritation, Category 2	H315	Causes skin irritation.
Serious eye damage/eye irritation, Category 2A	H319	Causes serious eye irritation.
Reproductive toxicity, Category 2	H361	Suspected of damaging the unborn child.
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336	May cause drowsiness or dizziness.
Specific target organ toxicity — Repeated exposure, Category 2	H373	May cause damage to organs (central nervous system) through prolonged or repeated exposure (Inhalation).
Aspiration hazard, Category 1	H304	May be fatal if swallowed and enters airways.

Full text of H statements : see section 16

2.2. Label elements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Danger
Hazard statements (GHS US) : Highly flammable liquid and vapor
May be fatal if swallowed and enters airways

Precautionary statements (GHS US)	<p>Causes skin irritation Causes serious eye irritation May cause drowsiness or dizziness Suspected of damaging the unborn child. May cause damage to organs (central nervous system) through prolonged or repeated exposure (Inhalation)</p> <p>: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. Keep container tightly closed. Ground/Bond container and receiving equipment. Use explosion-proof electrical, lighting, ventilating equipment. Do not breathe mist, spray, vapors. Wash hands, forearms and face thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves. If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice or attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention. If exposed or concerned: Get medical advice/attention. In case of fire: Use Dry chemical, CO2, alcohol-resistant foam or waterspray to extinguish. Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up. Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.</p>
-----------------------------------	--

2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

2.4. Hazards not otherwise classified

No additional information available

2.5. Unknown acute toxicity

No additional information available

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

SkyTest

Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Toluene	CAS-No.: 108-88-3	49	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 3, H412
Isopropyl alcohol	CAS-No.: 67-63-0	48	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Potassium hydroxide	CAS-No.: 1310-58-3	< 2	Acute Tox. 4 (Oral), H302 Skin Corr. 1A, H314
Naphtholbenzein	CAS-No.: 145-50-6	< 1	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

SECTION 4 First aid measures

4.1. Description of necessary first-aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention. First aider: Pay attention to self-protection. Never give anything by mouth to an unconscious person. Give artificial respiration if necessary. Induce artificial respiration with mask fitted with one-way valve or other suitable device but not mouth-to-mouth.
First-aid measures after inhalation	: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If the victim is unconscious : Lay in a stable manner on victim's side. Induce artificial respiration with mask fitted with one-way valve or other suitable device; not mouth-to-mouth. Call a physician immediately.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin areas with mild soap and water, followed by warm water rinse. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth and spit the fluids out. Do NOT induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Call a physician immediately.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation	: Causes damage to organs (nervous system) through prolonged or repeated exposure (Inhalation). May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: May cause irritation to skin.
Symptoms/effects after eye contact	: Causes serious eye irritation. Stinging, redness, itching, tears, blurred vision, swelling.
Symptoms/effects after ingestion	: May be fatal if swallowed and enters airways. Ingestion may cause nausea, vomiting and diarrhea. During vomiting high danger of aspiration.
Most Important Symptoms/Effects	: May be fatal if swallowed and enters airways. Vapors may cause drowsiness and dizziness. Causes skin and eye irritation.

SkyTest

Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Chronic symptoms : Causes damage to organs (central nervous system) through prolonged or repeated exposure (inhalation). Suspected of damaging the unborn child.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment : IF exposed: Call a POISON CENTER or doctor/physician.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Carbon dioxide. Dry powder. Foam.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard : Highly flammable liquid and vapor.
Explosion hazard : Vapors are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapors.
Hazardous decomposition products in case of fire : Toxic fumes may be released. Carbon dioxide. Carbon monoxide.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection. Move containers from fire area if it can be done without personal risk. Use water spray or fog for cooling exposed containers. Large fires: Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Withdraw immediately in case of rising sound from venting devices or discoloration from tank. ALWAYS stay away from tanks engulfed in fire. For a massive fire, use unmanned hose holders or monitor nozzles, or withdraw from the area and allow fire to burn. Prevent fire-fighting water from entering environment.
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Avoid all personal contact including breathing in the mist, spray, vapors. Do not take actions involving personal risks. Absorb spillage to prevent material-damage. Stop leak if safe to do so. Notify authorities if product enters sewers or public waters.

For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.
Emergency procedures : Evacuate the danger area. If outdoors, move to an area upwind of the danger area. Avoid breathing mist, spray, vapors, gas. If possible without taking personal risks, Remove ignition sources, ventilate area. No open flames, no sparks, and no smoking. Prevent other non-emergency personnel from entering the danger area.

For emergency responders

Protective equipment : Wear the recommended personal protective equipment. Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures : Evacuate unnecessary personnel. Ventilate spillage area. Stop leak if safe to do so. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. All equipment used when handling the product must be grounded.
Environmental precautions : Do not let the product reach soil, drains, sewers, or surface and ground water. Notify authorities if product enters sewers or public waters.

6.2. Methods and materials for containment and cleaning up

For containment	: Contain with non-combustible inert absorbent.
Methods for cleaning up	: Small spill: Take up in non-combustible inert absorbent and place into container for disposal. For large spills, confine the spill in a dike and charge it with wet sand or earth for subsequent safe disposal. Use non-sparking tools. Contaminated absorbent material may pose the same hazard as the spilt product. Decontaminate surfaces and equipment with water and detergent. Until a sufficient level of dilution is achieved, the decontamination water may pose the same hazards as the product. This material and its container must be disposed of in a safe way, and as per local legislation.

For further information refer to section 8: "Exposure controls/personal protection", For further information refer to section 13

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station. Wear personal protective equipment. Do not breathe mist, spray, vapors, gas. Do not get in eyes, on skin, or on clothing. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. Use explosion-proof equipment in any process generating vapors, gas air mixtures above the Lower Explosive Limit (refer to Section 9). Handling this product may result in electrostatic accumulation. Use proper grounding procedures. Floors, walls and other surfaces in the hazard area must be cleaned regularly.
Hygiene measures	: Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including incompatibilities

Storage conditions	: Store in a cool, dry and well-ventilated area away from incompatible substances. Store at room temperature. Keep only in original container. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. Keep container closed when not in use. Stored containers should be periodically checked for general condition and leakage.
Incompatible materials	: Strong acids. Oxidizing agents. Chlorine. Acetaldehyde. Hydrochloric acid. Isocyanates. Nitrogen tetroxide. Will attack some plastic, rubber, and coatings.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

Toluene (108-88-3)

USA - ACGIH - Occupational Exposure Limits

Local name	Toluene
ACGIH OEL TWA	20 ppm
Remark (ACGIH)	TLV® Basis: CNS, Hearing & Visual impair; Female repro system eff; Pregnancy loss. Notations: OTO (Ototoxicant); A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2025

USA - ACGIH - Biological Exposure Indices

Local name	Toluene
------------	---------

Toluene (108-88-3)	
BEI	0.3 mg/g Kreatinin Parameter: o-Cresol - Medium: urine - Sampling time: End of shift - Notations: B 0.02 mg/l Parameter: Toluene - Medium: blood - Sampling time: Prior to last shift of workweek 0.03 mg/l Parameter: Toluene - Medium: urine - Sampling time: End of shift
Regulatory reference	ACGIH 2025
USA - OSHA - Occupational Exposure Limits	
Local name	Toluene
OSHA PEL TWA	200 ppm
OSHA PEL C	300 ppm
Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift	500 ppm 10 mins.
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-2
Isopropyl alcohol (67-63-0)	
USA - ACGIH - Occupational Exposure Limits	
Local name	2-Propanol
ACGIH OEL TWA	491 mg/m ³
	200 ppm
ACGIH OEL STEL	984 mg/m ³
	400 ppm
Remark (ACGIH)	TLV® Basis: Eye & URT irr; CNS repair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2025
USA - ACGIH - Biological Exposure Indices	
Local name	2-Propanol
BEI	40 mg/l Parameter: Acetone - Medium: urine - Sampling time: End of shift at end of workweek - Notations: B, Ns
Regulatory reference	ACGIH 2025
USA - OSHA - Occupational Exposure Limits	
Local name	Isopropyl alcohol
OSHA PEL TWA	980 mg/m ³
	400 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
Potassium hydroxide (1310-58-3)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Potassium hydroxide
ACGIH OEL C	2 mg/m ³
Remark (ACGIH)	TLV® Basis: Eye, Skin & URT irr
Regulatory reference	ACGIH 2025

SkyTest

Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

8.2. Appropriate engineering controls

Appropriate engineering controls	: Ensure good ventilation of the work station. Use general ventilation, local exhaust ventilation, or process enclosure to keep the airborne concentrations below the permissible exposure limits. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.
Environmental exposure controls	: Avoid release to the environment. Take measures to reduce or limit air emissions and releases to soil and the aquatic environment.

8.3. Individual protection measures, such as personal protective equipment

Personal protective equipment:

Personal protective equipment should be chosen according to national standards and in discussion with the supplier of the protective equipment. Wear recommended personal protective equipment.

Materials for protective clothing:

Wear fire/flame resistant/retardant clothing.

Hand protection:

Protective gloves against chemicals (EN 374). Butyl rubber. Polyvinylalcohol (PVA). Polyvinylchloride (PVC). Nitrile rubber

Eye protection:

Chemical goggles or face shield

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Wear respiratory protection. Use a positive pressure self-contained breathing apparatus (SCBA).

Personal protective equipment symbol(s):



SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Liquid
Color	: Blue
Odor	: No data available
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 82 °C / 180 °F
Flash point	: 4 – 12 °C / 40-53 °F
Flammability (solid, gas)	: Highly flammable liquid and vapor.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: 0.8 – 0.85
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available

SkyTest

Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Decomposition temperature : No data available
Viscosity, kinematic : No data available
Explosion limits : No data available
Particle characteristics : No data available

Toluene

Particle characteristics	No data available
--------------------------	-------------------

Isopropyl alcohol

Particle characteristics	No data available
--------------------------	-------------------

Naphtholbenzein

Particle characteristics	No data available
--------------------------	-------------------

Potassium hydroxide

Particle characteristics	No data available
--------------------------	-------------------

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10 Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapor.

10.2. Chemical stability

Stable under normal conditions of use.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. No flames, no sparks. Eliminate all sources of ignition. Incompatible materials.

10.5. Incompatible materials

Strong acids. Oxidizing agents. Chlorine. Acetaldehyde. Hydrochloric acid. Isocyanates. Will attack some plastic, rubber, and coatings. Nitrogen tetroxide.

10.6. Hazardous decomposition products

Thermal decomposition generates: Carbon dioxide. Carbon monoxide.

SECTION 11 Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Toluene	
LD50 oral rat	5580 mg/kg body weight
LD50 dermal rabbit	> 5000 mg/kg body weight
LC50 Inhalation - Rat	12.5 mg/l
Isopropyl alcohol	
LD50 oral rat	5840 mg/kg body weight
Potassium hydroxide	
LD50 oral rat	333 – 388 mg/kg body weight
Skin corrosion/irritation	: Causes skin irritation.
Potassium hydroxide	
Specific concentration limits	Skin Corr. 1A; H314: C ≥ 5 % Skin Corr. 1B; H314: 2 % ≤ C < 5 % Skin Irrit. 2; H315: 0,5 % ≤ C < 2 %
Serious eye damage/irritation	: Causes serious eye irritation.
Potassium hydroxide	
Specific concentration limits	Eye Irrit. 2; H319: 0,5 % ≤ C < 2 %
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Toluene	
IARC group	3 - Not classifiable
Isopropyl alcohol	
IARC group	3 - Not classifiable
Reproductive toxicity	: Suspected of damaging the unborn child.
Toluene	
LOAEL (animal/female, F0/P)	520 mg/kg body weight
STOT-single exposure	: May cause drowsiness or dizziness.
Toluene	
STOT-single exposure	May cause drowsiness or dizziness.
Isopropyl alcohol	
STOT-single exposure	May cause drowsiness or dizziness.
Naphtholbenzein	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: May cause damage to organs (central nervous system) through prolonged or repeated exposure (Inhalation).

SkyTest

Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Toluene	
LOAEL (oral,rat,90 days)	1250 mg/kg body weight
NOAEL (oral,rat,90 days)	625 mg/kg body weight
NOAEC (inhalation,rat,vapor,90 days)	2.355 mg/l air
STOT-repeated exposure	May cause damage to organs (central nervous system) through prolonged or repeated exposure (Inhalation).

Aspiration hazard : May be fatal if swallowed and enters airways.

SkyTest	
Viscosity, kinematic	No data available
Toluene	
Viscosity, kinematic	No data available
Isopropyl alcohol	
Viscosity, kinematic	No data available
Naphtholbenzein	
Viscosity, kinematic	No data available
Potassium hydroxide	
Viscosity, kinematic	No data available

Symptoms/effects after inhalation : Causes damage to organs (nervous system) through prolonged or repeated exposure (Inhalation). May cause drowsiness or dizziness.

Symptoms/effects after skin contact : May cause irritation to skin.

Symptoms/effects after eye contact : Causes serious eye irritation. Stinging, redness, itching, tears, blurred vision, swelling.

Symptoms/effects after ingestion : May be fatal if swallowed and enters airways. Ingestion may cause nausea, vomiting and diarrhea. During vomiting high danger of aspiration.

Most Important Symptoms/Effects : May be fatal if swallowed and enters airways. Vapors may cause drowsiness and dizziness. Causes skin and eye irritation.

Chronic symptoms : Causes damage to organs (central nervous system) through prolonged or repeated exposure (inhalation). Suspected of damaging the unborn child.

SECTION 12 Ecological information

12.1. Ecotoxicity

Hazardous to the aquatic environment, short-term (acute) : Very toxic to aquatic life

Hazardous to the aquatic environment, long-term (chronic) : Toxic to aquatic life with long lasting effects

Toluene	
LC50 - Fish [1]	5.5 mg/l
LOEC (chronic)	2.76 mg/l
NOEC (chronic)	0.74 mg/l
NOEC chronic fish	1.39 mg/l
NOEC chronic crustacea	0.74 mg/l

SkyTest

Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Isopropyl alcohol	
LC50 - Fish [1]	10000 mg/l
LC50 - Fish [2]	9640 mg/l
Naphtholbenzein	
LC50 - Fish [1]	0.107 mg/l
EC50 96h - Algae [1]	0.024 mg/l

12.2. Persistence and degradability

SkyTest	
Persistence and degradability	Not rapidly degradable
Toluene	
Persistence and degradability	Rapidly degradable
Isopropyl alcohol	
Persistence and degradability	Not rapidly degradable
Naphtholbenzein	
Persistence and degradability	Not rapidly degradable
Potassium hydroxide	
Persistence and degradability	Not rapidly degradable

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Ozone : Not classified
Fluorinated greenhouse gases : No

SECTION 13 Disposal considerations

Regional waste regulation : Disposal must be done according to official regulations.
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations : Disposal must be done according to official regulations.
Product/Packaging disposal recommendations : Dispose of this material and its container at hazardous or special waste collection point. Refer to all applicable national, international and local regulations or provisions.
Additional information : Flammable vapors may accumulate in the container. Do not re-use empty containers.
Ecological waste information : Avoid release to the environment.

SECTION 14 Transport information

In accordance with DOT / IMDG / IATA

SkyTest

Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

DOT	IMDG	IATA
14.1. UN number		
UN1993	1993	1993
14.2. Proper Shipping Name		
Flammable liquids, n.o.s. (Toluene and Isopropyl Alcohol)	FLAMMABLE LIQUID, N.O.S. (Toluene and Isopropyl Alcohol)	Flammable liquid, n.o.s. (Toluene and Isopropyl Alcohol)
14.3. Transport hazard class(es)		
3	3	3
14.4. Packing group		
II	II	II
14.5. Environmental hazards		
	Marine pollutant: Yes	
No supplementary information available		

14.6. Transport in bulk

Not applicable

14.7. Special precautions for user

DOT

UN-No. (DOT) : UN1993
DOT Packaging Exceptions (49 CFR 173.xxx) : 150
DOT Packaging Non Bulk (49 CFR 173.xxx) : 202
DOT Packaging Bulk (49 CFR 173.xxx) : 242
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L
DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

IMDG

Special provision (IMDG) : 274
Limited quantities (IMDG) : 1 L
Excepted quantities (IMDG) : E2
Packing instructions (IMDG) : P001
IBC packing instructions (IMDG) : IBC02
Tank instructions (IMDG) : T7
Tank special provisions (IMDG) : TP1, TP28, TP8
EmS-No. (Fire) : F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS
EmS-No. (Spillage) : S-E - SPILLAGE SCHEDULE Echo - FLAMMABLE LIQUIDS, FLOATING ON WATER
Stowage category (IMDG) : B

IATA

PCA Excepted quantities (IATA) : E2
PCA Limited quantities (IATA) : Y341
PCA limited quantity max net quantity (IATA) : 1L
PCA packing instructions (IATA) : 353

SkyTest

Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

PCA max net quantity (IATA) : 5L
CAO packing instructions (IATA) : 364
CAO max net quantity (IATA) : 60L
ERG code (IATA) : 3H

SECTION 15 Regulatory information

15.1. Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Toluene	CAS-No. 108-88-3	49%
Isopropyl alcohol	CAS-No. 67-63-0	48%

Toluene (108-88-3)

Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ	1000 lb
-----------	---------

Potassium hydroxide (1310-58-3)

CERCLA RQ	1000 lb
-----------	---------

15.2. International regulations

CANADA

Toluene (108-88-3)

Listed on the Canadian DSL (Domestic Substances List)

Isopropyl alcohol (67-63-0)

Listed on the Canadian DSL (Domestic Substances List)

Naphtholbenzein (145-50-6)

Listed on the Canadian DSL (Domestic Substances List)

Potassium hydroxide (1310-58-3)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

Toluene (108-88-3)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Isopropyl alcohol (67-63-0)

Listed on INSQ (Mexican National Inventory of Chemical Substances)


Naphtholbenzein (145-50-6)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Potassium hydroxide (1310-58-3)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

15.3. State regulations

 **WARNING:** This product can expose you to Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16 Other information

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Issue date : 5/7/2025

Full text of hazard classes and H-statements

H225	Highly flammable liquid and vapor
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H361	Suspected of damaging fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.